


Dromex



CUT5 IMPACT GLOVE

EN 388: 2016
+ A1:2018



4442CP



52LSTPV

Description

Dromex® 52#LSTPV HI-VI, high visibility gloves consist of a 100% Dromex® Cut 5 fibre with PU coating on the palm area and innovative TPV impact protection on the back and thumb provides protection against cut, abrasion and impact hazards.

Features excellent dexterity, enhanced power grip, lint free construction and UV resistance when exposed to light. For use in industries such as automotive, steel/glass, assembling, warehousing, mining, construction work, police and military.

Special Instructions

Although the manufacturer has examined these gloves under the system for ensuring quality of production by means of monitoring and inspection, we recommend that all gloves should be thoroughly inspected before use to ensure no damage is present.

None of the materials or processes used in the manufacture of these products are known to be harmful to the wearer. The gloves and information contained herein are designed to accommodate the basic safety requirements and standards for Personal Protective Equipment. Actual conditions of use cannot be directly simulated in a test environment, therefore it is the responsibility of the user and not the manufacturer or supplier to determine the suitability for intended use.

Compliance & Conformity

Complies with the requirements of CE type examinations, approved to EN420 ISO 21420:2020 for innocuousness, and EN 388:2016 + A1:2018 (4,4,4,2,C,P) standard for Mechanical Risks with compliance to PPE Regulation (EU) 2016/425.

Specifications

Style: Pu palm dipped with TPV (Thermoplastic vulcanizate) knuckle and finger protection
 Liner: 100% Dromex® Cut 5
 Palm: PU (Polyurethane) coated 1.5 mm ± 5 %
 Back: 100% Dromex® Cut 5 fibre 1mm ± 5 % with TPV knuckle and fingers
 Cuff: Hook and Loop closure for enhanced fit
 Mass: ±140 g per glove (size 10)


Packaging, Storage & Obsolescence

Packed 12 pairs per bundle and 120 pairs per carton for shipping. Store in a cool, dry place. Stored correctly, the gloves physical properties will not change for up to three years.



Cleaning & Maintenance

Gloves should not be left in a contaminated condition if re-use is intended especially if potential hazards exist. Before removal from the hands excess contaminant should first be removed from the glove. Should this not be possible, it is advisable to ease left and right hand gloves off using the gloved hand and remove the gloves without the contaminant contacting the bare hands. The gloves may then be decontaminated as indicated below:



In order to maximise the glove life cycle, we recommend the mildest possible cleaning conditions in terms of temperature, chemicals and cycle duration.

Due to a wide variety of possible constructions and combinations with other materials we recommend to always consult your professional cleaning service to determine the best suitable cleaning method.

Disposal

All industrial waste should be disposed of correctly according to local regulations and good disposal practice. Gloves should be disposed of considering the hazardous substances they were used for. Please consider recycling.


Sizes Available

Code	Size	Palm Width	Cuff Colour
52LSTPV-8	S/M	95mm (±2mm)	Yellow
52LSTPV-9	M/L	100mm (±2mm)	Brown
52LSTPV-10	L/XL	105mm (±2mm)	Black

* As per the EN420 standard, actual measurement of gloves are determined by the manufacturer, taking into account the behaviour of the glove material, its thickness (such as leather gloves, PVC gloves etc), elasticity and the intended use.

* Sizing charts only serve as a guide. Sizes and measurements are for reference only. In order to make an informed decision, always try on the gloves as each glove features a unique construction to accommodate a wearer's preferences.

Measurement Guide



Materials



1. Wing thumb
2. TPV padding in fingers
3. 5cm Neoprene cuff with Hook and Loop closure