


Dromex



NITRILE PALM COATED GLOVES

EN 388: 2003



4131



NITROLITE

Description

Dromex® Nitrolite, smooth finish palm coated nitrile gloves, provide hands with excellent grip performance in wet, oily and dry environments.

The nylon liner provides high dexterity, comfort and fit, whilst the nitrile coating protects the hand from high abrasion and cut resistance with strong tear resistant properties.

Suitable for applications where hand protection is required in manufacturing, and assembly, material handling and general maintenance industries.

Special Instructions

Although the manufacturer has examined these gloves under the system for ensuring quality of production by means of monitoring and inspection, we recommend that all gloves should be thoroughly inspected before use to ensure no damage is present.

None of the materials or processes used in the manufacture of these products are known to be harmful to the wearer. The gloves and information contained herein are designed to accommodate the basic safety requirements and standards for Personal Protective Equipment. Actual conditions of use cannot be directly simulated in a test environment, therefore it is the responsibility of the user and not the manufacturer or supplier to determine the suitability for intended use.

Compliance & Conformity

Complies with the requirements of CE type examinations EN 420 for innocuousness, EN 388 for Mechanical Risks (4,1,3,1). Quality System conforms to ISO 9001:2008.

Specifications

Style: Palm and finger coated nitrile gloves
 Liner: Grey nylon
 Palm: Nitrile coated 0,2 mm ± 5%
 Back: 0,1 mm ± 5%
 Cuff: Nylon composite knitted wrist
 Mass: 44 ± g per pair (size 10)

Packaging, Storage & Obsolescence


Nitrolite gloves are packed in individual polybags and sold as 120 pairs per carton for shipping.
 Store in a cool, dry, dark place.
 Stored correctly, the gloves physical properties will not change for up to three years.



Cleaning & Maintenance

Gloves should not be left in contaminated condition if re-use is intended especially if potential hazards exist. Before removal from the hands excess contaminant should first be removed however, should this not be possible, it is advisable to ease left and right hand gloves off using the gloved hand and remove the gloves without the contaminant contacting the bare hands.

The gloves may then be decontaminated as indicated below.



In order to maximise the glove life cycle, we recommend the mildest possible cleaning conditions in terms of temperature, chemicals and cycle duration.

Due to a wide variety of possible constructions and combinations with other materials we recommend to always consult your professional cleaning service to determine the best suitable cleaning method.

Disposal

All industrial waste should be disposed of correctly according to local regulations and good disposal practice. Gloves should be disposed of considering the hazardous substances they were used for. Please consider recycling.

Sizes Available


Code	Size	Palm Length	Cuff Colour
NITROLITE-7	XS/S	90mm (±2mm)	Red
NITROLITE-8	S/M	95mm (±2mm)	Yellow
NITROLITE-9	M/L	100mm (±2mm)	Brown
NITROLITE-10	L/XL	105mm (±2mm)	Black

* As per the EN420 standard, actual measurement of gloves are determined by the manufacturer, taking into account the behaviour of the glove material, its thickness (such as leather gloves, PVC gloves etc), elasticity and the intended use.

* Sizing charts only serve as a guide. Sizes and measurements are for reference only. In order to make an informed decision, always try on the gloves as each glove features a unique construction to accommodate a wearer's preferences.

Marking

Measurement Guide



Materials



1. Wing thumb
2. Nitrile coated fingers & palm
3. Knitted wrist