


Dromex



NITRILE COATING GLOVE
#57



#57



Description

Dromex® 100% CUT5 gloves consists of a 100% Dromex® Cut5 outer liner, reinforcing the HCT (Hybrid coating technology) multilayer nitrile coating that provides protection against cut, abrasion and contact heat resistance for 15 seconds at 100°C. For use in industries such as automotive, assembling, steel and glass sheet handling, mining, construction work, chemical handling and oil and gas.

The #57 gloves features a reinforced thumb and index finger whilst, the HCT nitrile coating on the palm gives excellent oil resistance performance.

Special Instructions

Although the manufacturer has examined these gloves under the system for ensuring quality of production by means of monitoring and inspection, we recommend that all gloves should be thoroughly inspected before use to ensure no damage is present.

None of the materials or processes used in the manufacture of these products are known to be harmful to the wearer. The gloves and information contained herein are designed to accommodate the basic safety requirements and standards for Personal Protective Equipment. Actual conditions of use cannot be directly simulated in a test environment, therefore it is the responsibility of the user and not the manufacturer or supplier to determine the suitability for intended use.

Compliance & Conformity

Complies with the requirements of CE type examinations EN 420 for innocuousness, EN 388 for compliance with directive 89/686/EEC Mechanical Risks (4,5,4,3) and EN 407:2004 Thermal Risks for Heat and Flame (X1XXXX). Quality System conforms to ISO 9001:2008 and environmental management system ISO 14001:2015 system certificates or acceptable equivalent.

Specifications

Style: Wing thumb, palm dipped glove
Liner: 100% Dromex® Cut5
Palm: HCT (Hybrid coating technology) multilayer Nitrile coating 1.2mm ± 5 %
Back: 100% Dromex® Cut5 1mm ± 5 %
Cuff: 100% Dromex® Cut5
Mass: ± 99g per glove (size 11)

Sizes Available

7-12

Packaging, Storage & Obsolescence


Packed 12 pairs per bundle and 120 pairs per carton for shipping. Store in a cool, dry place. Stored correctly, the gloves physical properties will not change for up to three years.



Cleaning & Maintenance

Gloves should not be left in a contaminated condition if re-use is intended especially if potential hazards exist. Before removal from the hands excess contaminant should first be removed from the glove. Should this not be possible, it is advisable to ease left and right hand gloves off using the gloved hand and remove the gloves without the contaminant contacting the bare hands.

The gloves may then be decontaminated as indicated below:



Dromex® Cut5 gloves have proven that dry cleaning as well as laundering are suitable cleaning methods.

- We recommend that no bleaching or oxidising ingredients or any fabric softeners be used.
- Recommended washing temperature is between 40°C and 60°C (104~140°F) with mild detergents.
- The drying process may cause felting on the fabric surface. Drying temperature should not exceed 70°C (158°F).

There is no remarkable impact on cut resistance during the normal life cycle of a glove however, depending on glove construction, staining and cleaning method, the differences in shrinkage, yarn strength and colour may occur. In order to maximise the glove life-cycle, we recommend the mildest possible cleaning conditions in terms of temperature, chemicals and cycle duration.

Disposal

All industrial waste should be disposed of correctly according to local regulations and good disposal practice. Gloves should be disposed of considering the hazardous substance they were used for. Please consider recycling.

Materials



1. Reinforced thumb & fingers
2. Nitrile coated palm & fingers
3. Winged thumb
4. Knitted wrist

Marking

