


# Dromex



LATEX COATING GLOVE  
59YSP

EN 388: 2003



4543



59YSP

## Description

Dromex® 59YSP gloves consists of a 100% Dromex® CUT5 fibre that is lint free, UV resistant and washable with textured natural rubber coated palm and fingers for superior wet and dry grip, provides protection against cut, abrasion and puncture.

An ideal glove for handling sheet metal, glass and much more.

Contact heat protection of the glove is based on the temperatures at which the wearer will feel no pain for at least 15 seconds and at a level 2 contact temperature of 250°C.

Designed for a multiple range of industries and risks exposure. An ideal glove for automotive, assembling, packaging, warehousing both indoor and outdoor where toughness and dexterity are needed.

## Special Instructions

Although the manufacturer has examined these gloves under the system for ensuring quality of production by means of monitoring and inspection, we recommend that all gloves should be thoroughly inspected before use to ensure no damage is present.

None of the materials or processes used in the manufacture of these products are known to be harmful to the wearer. The gloves and information contained herein are designed to accommodate the basic safety requirements and standards for Personal Protective Equipment. Actual conditions of use cannot be directly simulated in a test environment, therefore it is the responsibility of the user and not the manufacturer or supplier to determine the suitability for intended use.

## Compliance & Conformity

Complies with the requirements of CE type examinations EN 420 for innocuousness, EN 388 for compliance with directive 89/686/EEC Mechanical Risks (4,5,4,3).  
Quality System conforms to ISO 9001:2008.

## Specifications

Style: Natural rubber coated palm and fingers  
Liner: 100% Dromex® Cut5 fibre  
Palm: 2mm ± 5 %  
Back: 1.5mm ± 5 %  
Cuff: Knit wrist  
Mass: ±142g per pair

## Sizes Available

8-11

## Packaging, Storage & Obsolescence

Packed 12 pairs per bundle and 120 pairs per carton for shipping.

Store in a cool, dry, dark place.


Stored correctly, the gloves physical properties will not change for up to three years.



## Cleaning & Maintenance

Gloves should not be left in a contaminated condition if re-use is intended especially if potential hazards exist. Before removal from the hands excess contaminant should first be removed from the glove. Should this not be possible, it is advisable to ease left and right hand gloves off using the gloved hand and remove the gloves without the contaminant contacting the bare hands.

The gloves may then be decontaminated as indicated below.



100% Dromex® Cut 5 gloves have proven that dry cleaning as well as laundering are suitable cleaning methods. We recommend that no bleaching or oxidising ingredients or any fabric softeners be used.

Recommended washing temperature is between 40°C and 60°C (104~140°F) with mild detergents.

The drying process may cause felting on the fabric surface.

Drying temperature should not exceed 70°C (158°F).

There is no remarkable impact on cut resistance during the normal life cycle of a glove. Depending on the glove construction, staining and cleaning method, the differences in shrinkage, yarn strength and colour may occur. In order to maximise the glove life cycle, we recommend the mildest possible cleaning conditions in terms of temperature, chemicals and cycle duration.

Due to a wide variety of possible constructions and combinations with other materials we recommend to always consult your professional cleaning service to determine the best suitable cleaning method.

## Disposal

All industrial waste should be disposed of correctly according to local regulations and good disposal practice. Gloves should be disposed of considering the hazardous substance they were used for. Please consider recycling.

## Materials



1. Wing thumb
2. Rubber coated palm & fingers
3. Knit wrist

## Marking

