


Dromex



PU5 GLOVE

EN 388:2016



3442C



PU5

Description

Dromex® PU5, lightweight, high mechanical strength, cut level 5 gloves with a PU (Polyurethane) coating provides superior dexterity and grip. The glove has high tear resistance properties protecting the hand against abrasion, cut and puncture hazards.

Designed for a multiple range of industries and risks exposure, this is an ideal glove for automotive and component assembly, packaging, warehousing and general handling where toughness and dexterity are needed.

Special Instructions

Although the manufacturer has examined these gloves under the system for ensuring quality of production by means of monitoring and inspection, we recommend that all gloves should be thoroughly inspected before use to ensure no damage is present.

None of the materials or processes used in the manufacture of these products are known to be harmful to the wearer. The gloves and information contained herein are designed to accommodate the basic safety requirements and standards for Personal Protective Equipment. Actual conditions of use cannot be directly simulated in a test environment, therefore it is the responsibility of the user and not the manufacturer or supplier to determine the suitability for intended use.

Compliance & Conformity

Complies with the requirements of CE type examinations EN 420 for innocuousness, approved to EN 388:2003 (3,5,4,2)* previous standard and EN 388:2016, (3,4,4,2,C)** revised standard for compliance with regulation (EU) 2016/425 for Mechanical Risks. Quality System conforms to ISO 9001:2015.

* *Dromex PU5 EN 388: 2003 is rated at a cut 5 level performance*

***Dromex PU5 EN 388:2016 is rated at a cut level 4, and class C performance due to the change of method in cut resistance testing methods.*

Specifications

Style: PU coated palm and fingers
Liner: HDPE (High Density Polyethylene), glass fibre and nylon
Palm: 1.1mm ± 5 %
Back: 1.0mm ± 5 %
Cuff: Knit wrist
Mass: 68± 5g Per pair (size 10)

Sizes Available

7-10

Packaging, Storage & Obsolescence

Packed in individual sealed plastic packets and 120 pairs per carton for shipping.


Store in a cool, dry, dark place. Stored correctly, the gloves physical properties will not change for up to three years.



Cleaning & Maintenance

Gloves should not be left in a contaminated condition if re-use is intended especially if potential hazards exist. Before removal from the hands excess contaminant should first be removed from the gloves. Should this not be possible, it is advisable to ease left and right hand gloves off using the gloved hand and remove the gloves without the contaminant contacting the bare hands.

The gloves may then be decontaminated as indicated below.



PU5 gloves have proven that dry cleaning as well as laundering are suitable cleaning methods. We recommend that no bleaching or oxidising ingredients or any fabric softeners be used. Recommended washing temperature is between 40°C and 60°C (104~140°F) with mild detergents. The drying process may cause felting on the fabric surface. Drying temperature should not exceed 70°C (158°F). There is no remarkable impact on cut resistance during the normal life cycle of a glove however, depending on glove construction, staining and cleaning method, the differences in shrinkage, yarn strength and colour may occur.

In order to maximise the glove life cycle, we recommend the mildest possible cleaning conditions in terms of temperature, chemicals and cycle duration.

Disposal

All industrial waste should be disposed of correctly according to local regulations and good disposal practice. Gloves should be disposed of considering the hazardous substances they were used for. Please consider recycling.

Materials



1. Wing thumb
2. PU coated palm & fingers
3. Knitted wrist

Marking



EN 388:2016



3442C

PU 5
SIZE 10