



PRODUCT CODE: RE0808

PRODUCT NAME: ENDURO-MAX

PRODUCT DESCRIPTION: Sport styled safety shoe

INFORMATION

| | |
|--|--|
| COLOUR | Black with grey only |
| SIZE RANGE | 4 – 13 (unisex, starts from a size 4) |
| ISO 20345 CLASSIFICATION | S1 – anti-static, energy absorption of seat region, resistance to fuel and oil |
| SLIP RESISTANCE CLASSIFICATION SRA / SRB / SRC | SRA – tested for slip resistance in environments of ceramic surfaces with soapy solution |
| CONSTRUCTION | Cemented |
| SABS | SABS approved and mark bearing |
| NRCS APPROVAL NO | NRCS/9002/262020/0088 |

MATERIALS

| | |
|------------------|--|
| UPPER | High quality durable mesh and Nubuck leather with rubber toe bumper for added scuff protection |
| SOLE | Dual density EVA and rubber |
| EYELETS | Nickel-free eyelets |
| LINING | Breathable and abrasion resistant taibrelle |
| TOE-CAP | 200J steel toe cap |
| FOOTBED (INSOLE) | Moulded polyurethane (PU); taibrelle mesh upper with contoured heel and arch |
| INSOLE BOARD | 3MR Ibitech non-woven insole board |

SPECIAL FEATURES

| | |
|-------|---|
| UPPER | Mesh and Nubuck upper offers superb ventilation |
| SOLE | <ul style="list-style-type: none">Dual density EVA and rubber which is heat resistance up to 300°C – however the upper is not suitable for heat applications.Moulded Thermoplastic polyurethane (TPU) sole insert offers torsional rigidity and lateral medial supportElectrostatic discharge (ESD) |
| OTHER | Non |

KEY FEATURES



SUGGESTED ENVIRONMENTS

General applications, hospitality, janitorial services, motor industry, production lines, transport.

