



ILULA CHAIN BLOCK

Robust & dependable chain block that is economical & lightweight

- Range from 500kg 20,000kg
- · Double pawl braking system
- Extra-thick asbestos-free friction plates
- Anti-slip hooks providing extra safety with heavy duty cast safety latches
- Full spares back-up for maintenance purposes
- Drop forged top & bottom hooks that can rotate 360°
- Designed to international standards. Generally compliant to SANS
- Units can be chained for any height of lift required
- · Overload protection available on request
- Each unit is tested to 125% of the rated capacity
- . Serial numbered for traceability
- Supplied with individual test certificate

Product Code	Capacity (ton)	Effort (kg)	Load Chain		Mass @ std	Mass for
			Diameter (mm)	No. of falls	3m lift (kg)	extra metre HOL (kg)
ICU005	0.5	20	6.0	1	8.0	1.7
ICU010	1.0	33	6.0	1	12.0	1.7
ICU015	1.5	37	8.0	1	18.0	2.3
ICU020	2.0	37	8.0	1	18.0	2.3
ICU030	3.0	39	8.0	2	25.0	3.7
ICU030S	3.0	42	10.0	1	28.0	3.1
ICU050	5.0	44	10.0	2	45.0	5.4
ICU100	10.0	44	10.0	4	79.0	9.7
ICU200	20.0	44 x 2	10.0	8	193.0	19.4



Available on request



ASSEMBLED & TESTED IN SOUTH AFRICA